



Akustikanlagen nach EN 54 –16
 Uhrenanlagen, analog und digital
 Lautsprecher für Beschallungsanlagen

Systèmes Audio d'évacuation EN 54 –16
 Horloges analogiques et digitales
 Haut-parleurs

Voice-Alarm according EN 54 –16
 Clock Systems, analogue and digital
 Loudspeaker



g+m elektronik ag
 CH-9245 Oberbüren
 www.gm-elektronik.ch

Multi-purpose scoreboard GM-117226-00 for Indoor- or Outdoor- (also with radio-remote-control)

Basic Module LED for 10 sports



Function:

- Display shows result, period and time in figures
 - Display for 2 penalty-times in min. and sec.
 - Display shows time-out, break, service and penalty with coloured dots
- Remote-control with Parallel-display (with cable or radio-controlled)

Design :

- One-side Scoreboard for wall-mounting
- Case aluminium, frontcover protected DIN 18032

Display	Colour	Artikel	Dimensions	Weight	Visibility
result, time, period	red	GM-117226-00	2200x1550x110 mm (B/H/T)	60,0 kg	120 m



Akustikanlagen nach EN 54 –16
Uhrenanlagen, analog und digital
Lautsprecher für Beschallungsanlagen

Systèmes Audio d'évacuation EN 54 –16
Horloges analogiques et digitales
Haut-parleurs

Voice-Alarm according EN 54 –16
Clock Systems, analogue and digital
Loudspeaker



g+m elektronik ag
CH-9245 Oberbüren
www.gm-elektronik.ch

Function:

- Match/Game time:** Count-up or down is indicated by four digits (minutes and seconds)
- Game stopped:** Indicated by green/red dot
- Score indication:** 000-999 (three digits per team)
- Period:** 1-9 (1 digit)
- Penalty-time:** display for 2 penalty-times each
- Serve/Foul:** Indicated by dots
- Time-Out:** By two yellow dots per team
- Fixed characters:** **H** (home team) and **G** (guests)
- Siren:** built-in. Sounds automatically at finished game, time-out and break/pause. By manually pressing a key, the siren can also sound at any requested time
- Front cover:** Non-reflective polycarbonate (DIN 18032)

Technical data:

- Case:** Aluminium profile
- Digits:** LED's
- Digit height:** score and time 250 mm, period 190 mm, red
- Dimensions:** 2000 x 1250 x 110 mm (W/H/D), weight 48 kg
- Visibility:** approx. 120 meters
- Conn. voltage:** 230 VAC, consumption 80 VA
- Ambient temp.:** 0° - +40°
- Siren :** Built in, 117 dB

- Options:**
- Remote-control radio controlled
 - Internal illumination
 - Local time (daytime)
 - Additional modules (penalty, foul)
 - Referee-Lamps red/green (Icehockey)