



Akustikanlagen nach EN 54 –16
Uhrenanlagen, analog und digital
Lautsprecher für Beschallungsanlagen

Systèmes Audio d'évacuation EN 54 –16
Horloges analogiques et digitales
Haut-parleurs

Voice-Alarm according EN 54 –16
Clock Systems, analogue and digital
Loudspeaker



g+m elektronik ag
CH-9245 Oberbüren
www.gm-elektronik.ch

Simple scoreboard LED 190 for indoor and outdoor

Simple LED scoreboard GM-117601-00



Function :

- Display shows result, period and time in figures
- Display shows time-out, break, service and penalty with coloured dots
- Easy remote-control, radio controlled

Design :

- One-side Scoreboard for wall-mounting
- Case aluminium, frontcover protected DIN 18032

Display	colour	Artikel	Dimensions	Weight	Visibility
Result, time, period	red	GM-117601-00	1400x900x50 mm (L/H/D)	14,0 kg	70 m



Akustikanlagen nach EN 54 –16
Uhrenanlagen, analog und digital
Lautsprecher für Beschallungsanlagen

Systèmes Audio d'évacuation EN 54 –16
Horloges analogiques et digitales
Haut-parleurs

Voice-Alarm according EN 54 –16
Clock Systems, analogue and digital
Loudspeaker



g+m elektronik ag
CH-9245 Oberbüren
www.gm-elektronik.ch

Function

Match/Game time:	Count-up or down is indicated by four digits (minutes and seconds)
Game stopped:	Indicated by red dot
Score indication:	000-999 (three digits per team)
Period:	1-9 (1 digit)
Penalty/Serve/Foul:	Indicated by dots
Time-Out:	By two red dots per team
Fixed characters:	H (home team) and G (guests)
Siren:	built-in. Sounds automatically at finished game, time-out and break/pause. By manually pressing a key, the siren can also sound at any requested time
Front cover:	Non-reflective polycarbonate (DIN 18032)

Technical data:

Case:	Aluminium profile
Digits:	Display LED
Digit height:	score and time 190 mm,
Dimensions:	1400 x 900 x 50 mm (W/H/D), weight 14 kg
Read. distance:	ca. 70m
Conn. voltage:	230 VAC, consumption 60 VA
Ambient temp.:	0° - +40°
Siren :	Built in, 117 dB