



Akustikanlagen nach EN 54 –16
 Uhrenanlagen, analog und digital
 Lautsprecher für Beschallungsanlagen
 Systèmes Audio d'évacuation EN 54 –16
 Horloges analogiques et digitales
 Haut-parleurs
 Voice-Alarm according EN 54 –16
 Clock Systems, analogue and digital
 Loudspeaker

Self adjusting (by TC) slave clocks with flat protection glass

Time Code-Minute Pulse 24-V – hours – minutes - Ø to 400 mm



Functions :

- Polarised minute impulses with Time-Code from Master clock
- The slave clocks will be automatically adjusted with the Time Code signal

Design :

- Single sided clock for surface mounting incl. surface mounting brackets
- Double sided clock incl. Mounting console for wall or ceiling mounting
- Black Arabic or Latin marks on white background, black hours and minutes hand
- Flat protection glass for better readability
- Housing anodised aluminium

Options:

- ball protection bars, Polycarbonate-cover
- housing, clock face, hands in different colours (extra charge)

Single Sided

Ø	Part Number
240 mm	111006-AL-TC-FG
300 mm	111018-AL-TC-FG
400 mm	111030-AL-TC-FG

Double Sided

Ø	Part Number
240 mm	111006-AL-DS-TC-FG
300 mm	111018-AL-DS-TC-FG
400 mm	111030-AL-DS-TC-FG



Akustikanlagen nach EN 54 –16
 Uhrenanlagen, analog und digital
 Lautsprecher für Beschallungsanlagen

Systèmes Audio d'évacuation EN 54 –16
 Horloges analogiques et digitales
 Haut-parleurs


Voice-Alarm according EN 54 –16
 Clock Systems, analogue and digital
 Loudspeaker



g+m elektronik ag
 CH-9245 Oberbüren
 www.gm-elektronik.ch

Technical Data:


Single sided Clocks



Ø	A	B	C	D		Gewicht	Ablesbarkeit
240	210	232	50	50		0,8 kg	20 m
300	280	305	50	50		1,1 kg	30 m
400	380	405	50	50		1.5 kg	40 m

measures in mm

Double Sided clocks



Ø	A	B	C	D	E	Gewicht	Ablesbarkeit
240	210	232	102	102	370	2,0 kg	20 m
300	280	305	102	102	445	2,6 kg	30 m
400	380	405	102	102	545	3,4 kg	40 m

measures in mm

Specification :

Power consumption : 7.5mA at 24V (single-sided), 15mA at 24V (double-sided)
 Ambient temperature : 0° to +40°
 Relative humidity : 85%
 Protection norm : IP 52

g+m elektronik ag
 CH-9245 Oberbüren
 T+ 41 (0)71 955 90 10
 F+ 41 (0)71 955 90 20

Externe Filialen Schweiz/Regional Swiss Offices:
 5504 Othmarsingen T +41 (0)62 896 02 08 F +41 (0)62 896 02 68
 1090 La Croix (Lutry) T +41 (0)21 791 63 06 F +41 (0)21 791 63 08
 www.gm-elektronik.ch adm@gm-elektronik.ch

Tochterfirmen im Ausland/Subsidiary Companies:
 g+m elektroakustik GmbH D-64646 Heppenheim
 g+m électronique S.A.R.L. F-21202 Beaune
 g+m audio-technologie B.V NL-4824 AT Breda