



Akustikanlagen nach EN 54 –16
 Uhrenanlagen, analog und digital
 Lautsprecher für Beschallungsanlagen

Systèmes Audio d'évacuation EN 54 –16
 Horloges analogiques et digitales
 Haut-parleurs

Voice-Alarm according EN 54 –16
 Clock Systems, analogue and digital
 Loudspeaker



Digital Clocks Aurea II for Indoor

Minute Pulse 24-V – 230 VAC - Hours – Minutes



Functions :

- Polarised Minute impulses from master Clock
- Polarised Minute impulses from master Clock with TC (self adjusting)
- Stand alone
- For all functions 230 VAC needed (Display)
- 72 h running reserve (Impulse memory)

Design :

- Single sided clock for surface mounting incl. surface mounting brackets
- Double sided clock incl. Mounting console for wall or ceiling mounting
- Display hours and minutes in red or green 58 mm (119405)
- Display seconds in red or green 45 mm (119415)
- housing black

Option:

- Radio Synchronisation DCF, GM-2022, operated as stand alone
- Temp.-sensor – add on (119497-809 operated as a Temperature Display)
- Time-Code-add on (SM-TC) operated as a self adjusted slave clock

Single Sided, Display red

Display	Type	Dimension
Std., Min.	119405-01	275x130x60 mm (B/H/T)
Std., Min., Sek.	119415-01	363x130x60 mm (B/H/T)

Double Sided, Display green

Display	Type	Dimension
Std., Min.	119405-00	275x130x60 mm (B/H/T)
Std., Min., Sek.	119415-00	363x130x60 mm (B/H/T)