



Akustikanlagen nach EN 54 –16  
 Uhrenanlagen, analog und digital  
 Lautsprecher für Beschallungsanlagen

Systèmes Audio d'évacuation EN 54 –16  
 Horloges analogiques et digitales  
 Haut-parleurs

Voice-Alarm according EN 54 –16  
 Clock Systems, analogue and digital  
 Loudspeaker



g+m elektronik ag  
 CH-9245 Oberbüren  
 www.gm-elektronik.ch

# Digital Clocks Lumex 12 for Indoor

Minute Pulse 24-V – 230 VAC – Hours – Minutes



Lumex-12



Lumex-12-S

## Functions :

- Polarised Minute impulses from master Clock
- Polarised Minute impulses from master Clock with TC (self adjusting)
- Stand alone
- For all functions 230 VAC needed (Display)
- 24 h running reserve (Impulse memory)

## Design :

- Single sided clock for surface mounting incl. surface mounting brackets
- Double sided clock incl. Mounting console for wall or ceiling mounting
- Display hours and minutes with LED 120 mm, Seconds 100 mm
- housing black

## Options :

- Radio Synchronisation DCF, GM-2022, operated as stand alone
- Temp.-sensor – add on (119497-809 operated as a Temperature Display)
- Time-Code-add on (SM-TC) operated as a self adjusted slave clock

## Single sided, Display red

Display	Type	Dimension	visibility
Hrs., Min.	Lumex-12	450x190x65 mm (W/H/D)	50 m
Hrs., Min., Sec.	Lumex-12-S	640x190x65 mm (W/H/D)	50 m