



Akustikanlagen nach EN 54 –16
 Uhrenanlagen, analog und digital
 Lautsprecher für Beschallungsanlagen

Systèmes Audio d'évacuation EN 54 –16
 Horloges analogiques et digitales
 Haut-parleurs

Voice-Alarm according EN 54 –16
 Clock Systems, analogue and digital
 Loudspeaker



g+m elektronik ag
 CH-9245 Oberbüren
 www.gm-elektronik.ch

Digital Clocks Lumex 6 for Indoor

Minute Pulse 24-V – 230 VAC – Hours – Minutes



Lumex-6



Lumex-6-S

Functions :

- Polarised Minute impulses from master Clock
- Polarised Minute impulses from master Clock with TC (self adjusting)
- Stand alone
- For all functions 230 VAC needed (Display)
- 24 h running reserve (Impulse memory)

Design :

- Single sided clock for surface mounting incl. surface mounting brackets
- Double sided clock incl. Mounting console for wall or ceiling mounting
- Display hours and minutes with LED 60 mm, Seconds 45 mm
- housing black

Options :

- Radio Synchronisation DCF, GM-2022, operated as stand alone
- Temp.-sensor – add on (119497-809 operated as a Temperature Display)
- Time-Code-add on (SM-TC) operated as a self adjusted slave clock

Single sided, Display red

Display	Type	Dimension	visibility
Hrs., Min.	Lumex-6	315x130x65 mm (W/H/D)	25 m
Hrs., Min., Sec.	Lumex-6-S	425x130x65 mm (W/H/D)	25 m