



Akustikanlagen nach EN 54 –16
 Uhrenanlagen, analog und digital
 Lautsprecher für Beschallungsanlagen

Systèmes Audio d'évacuation EN 54 –16
 Horloges analogiques et digitales
 Haut-parleurs

Voice-Alarm according EN 54 –16
 Clock Systems, analogue and digital
 Loudspeaker

Alphanumeric Digital Clocks Datex II/III for Indoor

Minute Pulse 24-V – 230 VAC – Hours – Minutes – Date



119442-53



119440-53



119444-53



119446-53

Functions :

- Polarised Minute impulses from master Clock
- Polarised Minute impulses from master Clock with TC (self adjusting)
- Stand alone
- For all functions 230 VAC needed (Display)
- 24 h running reserve (Impulse memory)

Design :

- Single sided clock for surface mounting incl. surface mounting brackets
- Double sided clock incl. Mounting console for wall or ceiling mounting
- Display hours and minutes with LED 60m, Seconds 45m
- housing aluminium

Options :

- Radio Synchronisation DCF, GM-2022, operated as stand alone
- Temp.-sensor – add on (119497-809 operated as a Temperature Display)
- Time- Code-add on (SM-TC) operated as a self adjusted slave clock

Single sided, Display red

Display	Type	Dimension	visibility
Hrs, Min, Date	119442-53	690x130x65 mm (W/H/D)	25 m
Hrs, Min, Date	119440-53	380x255x65 mm (W/H/D)	25 m
Hrs, Min, Date	119446-53	880x130x65 mm (W/H/D)	25 m
Hrs, Min, Date	119444-53	570x255x65 mm (W/H/D)	25 m